



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING: 125 VAC RMS
- 2. CURRENT RATING: 1.5AMP
- 3. CONTACT RESISTANCE: 100MILLIOHMS MAX
- 4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @500 VDC
- 5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

- 1. STORAGE: -40° TO +85°
- 2. OPERATION: 0° TO 70°

MECHANICAL:

- 1. MATERIAL: ABS

SYM	Number	Bill No. of Alteration	Signature	Date
Drawn				Tolerance
Checked				±0.10
Approved				±0.15
				±0.20
				±0.25
				±0.30
				±0.35
				±0.40
				±0.45
				±0.50
				±0.55
				±0.60
				±0.65
				±0.70
				±0.75
				±0.80
				±0.85
				±0.90
				±0.95
				±1.00
				Angle
				±30°

Material			Angles	Projection	Sheet	1 OF 1	Version: A/0	Scale	Unit	Item No.	1 1 1 1 1 1
A4			0°	⊙			A4	X:1	mm	Part Name	Keystone Holder
			90°	⊙						ERP	
			45°	⊙						Part No.	
			30°	⊙							
			15°	⊙							
			0°	⊙							