





REV.	DESCRIPTION	ENG.	APPROVAL



(Dust Cover)



ELECTR CAL:

- 1.CONTACT RESISTANCE: 20m OHM
- 2.INSULATION RESISTANCE: <= 250M OHM @100 V DC
- 3.WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ, I MIN
- 4.CAT6 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

- 1.STORAGE: -40°/ +70°
- 2.OPERATION: -10°/ +60°

MECHANICAL:

- 1.PLASTIC MATERIAL: NEW PC
- 2.GOLD PINS: PHOSPHOR BRONZE, GOLD PLATING 3U
- 3.TERMINAL PINS: PHOSPHOR BRONZE, ZIN PLATING
- 4.RJ45 CONTACT LIFE: 750 TIMES MIN
- 5.IDC TERMINAL LIFE: 250 TIMES MIN

TYPE:

- 1.CAT6 UNSHIELDED RJ45 KEYSTONE JACK

TITLE:				
RJ45 Keystone Jack				
CUSTOMER:			Date	23.01.10
Item No: WT-2017			Unit	mm
W & T Telecommunication Co., Ltd.			Scale	1:1
			Sheet	1 of
TOLERANCE(MM)		Projection	A4	
X	±0.5mm	Size.	A	
X.X	± 0.20mm	REV.	A	
X.XX	±0.15mm			